



P-621

Glass Cloth / Flame Retardant Electrical Tape

APPLICATION

Super-strong, flame resistant tape engineered expressly for applications where high temperatures are present - harness wrapping wire to be used around ovens or hearths; splicing or holding components subjected to high process temperatures. Approved for use as an aircraft cargo liner tape.

Also recommended for heavy-duty bundling - especially where flame resistance is vital - and to protect stainless steel and other polished metal surfaces from splatter during welding or soldering.

FEATURES AND BENEFITS

- High tensile strength.
- Provides a heat bonding adhesive - after application of heat, tape adhesion increases up to four times.
- Government specification FAR Part 25. Section 853.

TECHNICAL DATA

Backing material	Glass Cloth
Adhesive	Rubber/resin, flame retardant
Color	Natural
Total tape thickness	7.5 mils / 0.191 mm
Tensile strength	170 lbs. per in. / 35.7 kg per cm
Adhesion to steel	65 oz. per in. / 725 gm per cm
Unwind @ 150 FPM	20 oz. per in. / 223 gm per cm
Gov't specification	FAR Part 25, Section 853

Note: The above are typical values and should not be used in writing specifications.

For Pricing and Information

please contact:

KIEPURA AVIATION CORP.

61 Church St.

Littleton, NH 03561

Tel: 603-444-3459 / Fax: 603-444-0790

Toll Free: 1-888-522-8273 (USA/Canada)

Email: jane@kiepuraaviation.com

www.kiepuraaviation.com