

P-55

Flame Retardant Double-Coated Cloth Tape

APPLICATION

Flame retardant construction. Engineered to meet stringent requirements of aviation industry - widely used for installing carpeting on interior floors and stairways of commercial aircraft.

Recommended for service wherever flame retardancy and/or a rugged, heavy-duty double-coated tape is demanded. Examples: fastening automotive interior carpeting and vinyls. splicing foils. plastics. metals. cloth or glass. Ideal for commercial and institutional carpet installation work. especially on rough surfaces such as concrete or unfinished wooden floors. Often used for mounting kick plates to mount trim strips where walls meet pre-hung ceiling.

FEATURES AND BENEFITS

- Adhesive is flame retardant. Meets Government spec FAR-Part 25 Section 853.
- Provides high quick-stick. with a good, strong bond that improves with age.
- High adhesion for fail-safe bonds under the most adverse environments and tensions.
- Cloth backing provides excellent strength and superior conformability.
- Quick, easy and clean to use!

TECHNICAL DATA

Backing material	Cotton cloth with flame retardant fungicide treatment
Adhesive	Cured rubber / resin, flame retardant
Color	White
Tape thickness	
With liner	17.0 mils / 0.432mm
Without liner	13.0 mils / 0.330mm
Adhesion to steel	105 oz. per in. / 1116 gm per cm
Gov't specification	FAR-Part 25 Section 853

Note: The above are typical values and should not be used in writing specifications.

For Pricing and Information

please contact:

KIEPURA AVIATION CORP.

61 Church St.

Littleton, NH 03561

Tel: 603-444-3459 / Fax: 603-444-0790

Toll Free: 1-888-522-8273 (USA/Canada)

Email: jane@kiepuraaviation.com

www.kiepuraaviation.com