


# 108FR

## **FR Double-Coated Cloth Tape**



**Carrier:** Cloth

Adhesive: Rubber

Liner: Blue LDPE

**Colors:** Natural or Black (adhesive color)

**Specifications:** FAA FAR 25.853(a)

> Boeing BMS 5-133, BAC5034-4 Sec 5.1a(1)(b)

Douglas DMS 1971 Lockheed LAC C-24-1257 Embraer MEP 06-048

Fokker FK05-121, FK05-197 Airbus ABD0031 Para 7.4 Bombardier DSC 91-8-1 & DSC 91-8-2

**Standard Sizes:** 48mm x 23m, 72mm x 23m

### **Applications**

- Carpet installation on interior floors and stairs of aircraft
- Acrylic plastic sheeting applications.

Mounting & holding for general shop & machine handling.

#### **Features Benefits**

<ul> <li>Cloth re</li> </ul>	inforcement	•	Good strength and elongation for easy
			tear, application and removal
		•	Conformable and moisture resistant
<ul> <li>Flame re</li> </ul>	etardant rubber-based adhesive	•	Clean removal from most surfaces
		•	Aggressive bond for secure hold
		•	Repositionable adhesive for easy installation

### **Physical Properties**

	Standard UOM	Metric UOM	Test Method
Total Thickness	15 mils	381 mic	ASTM D-1000
Adhesion to Steel (air)	60 oz/in	6.57 N/cm	PSTC-101
Tensile Strength	55 lb/in	96.32 N/cm	ASTM D-1000
Weight	13 oz/sq yd	472.9 g/m <sup>2</sup>	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 ℃	
Exiting Time	1.5 sec		FAR 25.853(a)
Burn Length	4.5"		FAR 25.853(a)
Drip Exiting	N/A		FAR 25.853(a)

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendation was prepared at bearing PLASTICS CONFORMION (25 Prolege Parkway Frainmin, wo 2005) by qualified technical personnier. to berry Plastics intowned in the analysis information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



For Pricing and Information please contact distributor: KIEPURA AVIATION CORP.

61 Church St. Littleton, NH 03561

Tel: 603-444-3459 / Fax: 603-444-0790 Toll Free: 1-888-522-8273 (USA/Canada)

Email: jane@kiepuraaviation.com www.kiepuraaviation.com