

8100



PATCO® 8100 Heavy-Duty Surface Protection Tape


APPLICATIONS

- Heavy-duty, long or short=term surface protection.
- Protective film for shot peening in metal cleaning operations.
- Anti-squeak, vibration and sound dampening for automotive and marine OEM.
- Surface protection for air foil and ground effects panels on racing cars and trucks.

FEATURES & BENEFITS

- · Highly elastic and very tough.
- · Abrasion resistant.
- Repositionable.
- High and low-temperature applications.
- Extra thickness for stay flat and dimensional stability.
- · Conformable and long lasting.
- Transparent for visual inspection.
- Easy to apply just press in place.
- Excellent for die-cutting.

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated with Liner Construction

Backing:

• Interior-Grade Aromatic Ployurethane

Adhesive:

Urethane-based

I iner

• 91# Coated Kraft Paper

Colors:

Transparent

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness Substrate Thickness Adhesion to Steel Tensile Strength Elongation (%) Operating Temperature Application Temperature	9 mils 7 mils 40 oz/in. 60 lb/in. 500 % -65°F to 300°F 50°F to 120°F	229 Microns 178 Microns 0.438 N/mm 10.508 N/mm	PSTC-33 PSTC-33 ASTM D-3330 ASTM D-3759

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility

For Pricing and Information please contact: KIEPURA AVIATION CORP.

61 Church St. Littleton, NH 03561

Tel: 603-444-3459 / Fax: 603-444-0790 Toll Free: 1-888-522-8273 (USA/Canada)

Email: jane@kiepuraaviation.com www.kiepuraaviation.com



^{**} Recommended storage conditions: 40-60% Humidity, 60°F-80°F