



Elastomeric Material Solutions Division
 1100 Governor Lea Road, Bear, DE 19701
 (302) 834-2100 (302) 834-4021 (Fax)
www.rogerscorp.com/aron

PRODUCT INFORMATION SHEET	
Reference MOX-Tape® :	604 - 1
ARLON® Product Number:	T2040-R004

PRODUCT DESCRIPTION

1.00" wide, 0.040" thick, red, triangular cross-section, silicone, self-fusing tape.
 Product is supplied in various yard-long roll lengths.
 Meets Commercial Item Description A-A-59163 (supersedes US Military Specification MIL-I-46852C) except for packaging.

Design / Construction

Rubber: Cured Self-fusing Silicone Rubber
Cross-Section 1.00" Wide Triangular
Interleave: 0.001" Mylar



<u>Rubber Thickness</u>	<u>Value</u>	<u>Method</u>
Overall Thickness:	0.040"	Arlon SQA-TMS-012

Product Color : Red tape with green guideline

TYPICAL PROPERTIES

<u>Product Properties</u>	<u>Value</u>	<u>Method</u>
Tensile Strength lb/in	1392	Arlon SQA-TMS-009
Elongation %	732	Arlon SQA-TMS-009
Tear Strength ppi	151	Arlon SQA-TMS-029
Durometer (Silicone Compound) Shore A Points	49	Arlon SQA-TMS-014
Specific Gravity (Silicone Compound) ---	1.2	Arlon SQA-TMS-024
Dielectric Strength volts/mil	498	Arlon SQA-TMS-020
Bond Strength lb/in	3.5	Arlon SQA-TMS-015
Water Absorption %	0.1	Arlon SQA-TMS-016

SHELF LIFE AND RECOMMENDED OPERATING TEMPERATURE

Product Shelf Life 12 months from DOM @ 70°F
Note: Shelf life is defined as the duration of time for which the product will meet the physical characteristics outlined on this page. It does not guarantee the product's usefulness in all applications.

Product Operating Temperature -60°F to +400°F

The data presented in this document represents typical values for the production material. Typical values should not be used for specification limits.

Please verify that any printed hard copy of this datasheet is current by referencing: www.rogerscorp.com/aron

The information contained in this Data Sheet is intended to assist you in designing with Rogers' ARLON Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' ARLON Materials for each application. The Rogers logo, Helping power, protect, connect our world and ARLON are trademarks of Rogers Corporation or one of its subsidiaries. ©2018 Rogers Corporation, All rights reserved. Printed in U.S.A., 0618-PDF, **Publication #202-173** For Pricing and Information please contact distributor:

Kiepura Aviation Corp.
 61 Church Street
 Littleton, New Hampshire 03561 USA

Tel: 603-444-3459
 Fax: 603-444-0790
jane@kiepuraaviation.com
www.kiepuraaviation.com



Toll Free: In the US & Canada
 888 KAC TAPE
 888 522 8273

Accredited according to
 ASA-100 and FAA AC 00-56B