

1100 Governor Lea Road, Bear, DE 19701 1.302.834.2100 • 1.302.834.4021 (Fax)

PRODUCT INFORMATION SHEET

Reference MOX-Tape®: SB00520 Arlon Product Number: T4020-R002

MFG Test Report to: MIL-I-22444C; P5189-3; DMS2186 TY1; RMS315 TY1; GE A50A493C; 5-00857; IBM 6084744

PRODUCT DESCRIPTION

Design / Construction

Cured self-fusing silicone rubber Side 1:

Substrate: 15% Sinusoidal fiberglass

Side 2: Cured self-fusing silicone rubber

0.001" Polyester film Interleave:

Rubber Thickness Method Value 0.50" Arlon SQA-TMS-012 Width

> 0.020" Arlon SQA-TMS-012 **Overall Thickness:**

Product Color: Red

TYPICAL PROPERTIES

Product Properties		<u>Value</u>	<u>Method</u>
Tensile Strength	psi	4062	Arlon SQA-TMS-048
Elongation	%	25	Arlon SQA-TMS-048
Durometer	Shore A Points	50	Arlon SQA-TMS-014
Specific Gravity		1.2	Arlon SQA-TMS-024
Dielectric Strength	volts/mil	577	Arlon SQA-TMS-020
Adhesion Strength	lb/in	3.5	Arlon SQA-TMS-047

SHELF LIFE AND RECOMENDED OPERATING TEMPERATURE

Product Shelf Life

12 months from DOM @ 70°F

Note: Shelf life is defined as the duration of time for which the product will meet the physical characteristics outlined on this page. It does not guarantee the product's usefulness in all applications.

Product Operating Temperature -60 to +400°F

> The data presented in this document represent typical values for the production material. The data should not be used to write, or in place of, material specifications. Please verify that any printed hard copy of this datasheet is current by referencing: http://www.rogerscorporation.com

> > Last Revised May 14, 2016 .

NOTE: The above properties are published as a guide only, and should not be used for specification without testing in your own laboratory.

For Pricing and Information please contact distributor:

Kiepura Aviation Corp.

61 Church Street Littleton, New Hampshire 03561 USA

Tel: 603-444-3459 Fax:603-444-0790 jane@kiepuraaviation.com www.kiepuraaviation.com



Toll Free: In the US & Canada **888 KAC TAPE** 888 522 8273