



E&H LAMINATING & SLITTING COMPANY

E&H #70-1C

PRESSURE SENSITIVE INSULATION COVER SPLICING TAPE

INTENDED USE: This tape is primarily used in the fabrication of insulation blanket covers and for the installation of insulation blankets. It may be used for sealing sewn seams and for closing fabrication slits or holes around brackets, conduits or other objects that may exist after installation.

CONSTRUCTION: White polyester film
10x10 visual scrim count with Fire Retardant Acrylic Pressure Sensitive Adhesive

PTSC-1 PEEL STRENGTH: On aluminum

15 Min.	Repositionaable
24 hour	52.4 oz/inch average
5 Day	92.8 oz/inch average

PSTC-31 Tensile Strength 23 lbs. / inch of width average

WEIGHT: 3.0 oz./square yard maximum

FLAMMABILITY:

Burn Length	2.2 inches maximum
Flame Time	0 Seconds
Drip Flame Time	No Drips

SHELF LIFE: Minimum of 18 months in cool, dry storage

PASSES SPECIFICATIONS:
FAR PART 25.853 (A,B)
BSS-7230 12 second vertical burn
BMS 5-149 Rev. D Type XI, Class 1 Grade C Form 1
BMS 5-149 Rev. D Type XI, Class 2 Grade C Form 1
BAMS 535-004 Rev. NC Type 1

E&H CO: As manufacturer warrants that the products described and presented herein are of merchantable quality, but does not warrant their fitness for any particular use or make any other warranty, expressed or implied. Liability of **E&H** under this warranty is limited to replacement of the products found to be defective, or, at its option, a refund of the purchase price.

**For Pricing and Information
please contact distributor:**
KIEPURA AVIATION CORP.
61 Church St.
Littleton, NH 03561
Tel: 603-444-3459 / Fax: 603-444-0790
Toll Free: 1-888-522-8273 (USA/Canada)
Email: jane@kiepuraaviation.com
www.kiepuraaviation.com