



9425FR

Interior Grade Moisture Barrier / Corrosion Protective Tape

FR Aromatic Ether Polyurethane with FR Hydrophobic Acrylic adhesive and PE Release Liner.

Aircraft corrosion protection. Abrasion guard. Floor seam protection for wet areas of aircraft. Seat track protection. Cargo area moisture protection.

- ◆ Lightweight & tough.
- ◆ Mold & fungus resistant.
- ◆ Flame-retardant, self-extinguishing.
- ◆ Contains no PBDEs (Polybrominated Biphenyl Ethers).
- ◆ Contains no PBBs (Polybrominated Biphenyls).
- ◆ Moderately aggressive, yet repositionable adhesive.
- ◆ No plasticizers.
- ◆ Can be die cut for custom applications.
- ◆ Clean removal - no residue.

Adhesive	Acrylic
Backing	Polyurethane
Adhesion (PSTC-1) –	
24 HR Aluminum	40 oz/in / 45 g/mm
24 HR BMS 4-20 Panel	40 oz/in / 45 g/mm
7 Days @ 160 ⁰ F Aluminum	53 oz/in / 59 g/mm
7 Days @ 160 ⁰ F BMS 4-20 Panel	65 oz/in / 73 g/mm
Adhesion to steel	35 oz/in / 39 g/mm
Elongation (ASTM D-3759)	490%
Puncture Resistance	11.7 lbs
Thickness (ASTM D-1000)	6.1 Mils / 0.155 mm
Water Vapor Transmission Rate	5.2 g/ 100 sq. in. / 24 hrs
Weight	5.0 oz / sq. yd. / 170 g/m ²
Specifications	Boeing BMS 8-346B Type 1 Class 3, EU 76/769/EEC, FAR 25.853(a)

Note: The above are typical values and should not be used in writing specifications

For Pricing and Information
please contact:

KIEPURA AVIATION CORP.

61 Church Street

Littleton, New Hampshire 03561 USA

Tel: 603-444-3459 / Fax: 603-444-0790

Toll Free: 1-888-522-8273 (USA/Canada)

Email: info@kiepuraaviation.com

www.kiepuraaviation.com

