

## P-306 VINYL PROTECTION TAPE

### APPLICATION

Heavy-duty polyvinyl chloride film tape engineered specifically for use as a **corrosion resistant covering of pipe and conduits** installed either above or below ground. Also used as a **moisture barrier** on floor panels of commercial aircraft.

### FEATURES AND BENEFITS

- High-tack, high-hold adhesive is resistant to bacteria and fungus...and provides an effective and lasting seal against moisture, corrosion, electrolytic action and chemical attack.
- High degree of bonding between adhesive and PVC minimizes shrinkage - permits narrow overlap settings when tape is applied with automatic equipment, which maximizes tape usage and minimizes tape waste.
- Easy and uniform release.
- Withstands considerable shock without abrasion or puncture.

### TECHNICAL DATA

Backing material	Polyvinyl chloride (PVC) film
Adhesive	Rubber-based
Color	Black, printed
Total tape thickness	10.0 mils/0.254 mm
Tensile strength	28 lbs. per in./5.00 kg per cm
Adhesion to steel	30 oz. per in./335 gm per cm
Flame retardancy	Will not support combustion
Temperature range for application	40° F to 150° F
after application	-35° F to 225° F
Approval for listing	International Association of Plumbing and Mechanical Officials' Directory

Note: The above are typical values and should not be used in writing specifications.

### STOCK SIZES

Refer to current price List.

Distributed By:

Kiepura Aviation Corp.



61 Church Street • Littleton, New Hampshire 03561-4701 USA  
Phone: 603 444 3459 • Fax: 603 444 0790 • USA/Canada 1 888 522 TAPE  
www.kiepuraaviation.com • info@kiepuraaviation.com