



Date: 12-08-08
ORIGINAL

E & H #743-BLK
PRESSURE SENSITIVE INSULATION COVER SPLICING TAPE

INTENDED USE: This tape is primarily used in the fabrication of insulation blanket covers and for the installation of insulation blankets. It may be used for sealing sewn seams and for closing fabrication slits or holes around brackets, conduits or other objects that may exist after installation.

CONSTRUCTION: Black coat polyvinyl fluoride film
10 x 10 visual scrim count with a highly fire retardant acrylic
pressure sensitive adhesive

180° PEEL STRENGTH PSTC-1 (ASTM D 3330):

24 Hours Conditioning on Aluminum

<u>ENGLISH</u>		<u>METRIC</u>	
Room Temp.	3.8 lbs./1" width	Room Temp.	16.72N /25mm
120°F/100%RH	3.9 lbs./1" width	48.89°C/100%RH	17.16N / 25mm
160°F	4.1 lbs./1" width	71.11°C	18.24N / 25mm
-65°F	3.6 lbs./1" width	-53.89°C	16.02N / 25mm

E&H Laminating & Slitting Company

138 Grand Street, Paterson, New Jersey 07501 ■ Tel: (973) 345-1725 ■ Fax: (973) 345-3224
www.ehlam.com ■ e-mail: info@ehlam.com